

PopPack LED NEW

Fast. Simple. Affordable.



**Replaces 1/2x36W
and 1/2x58W T26**

**Up to 67%
Energy saving**



Key features



Performance

- LED one for one replacement for single and twin T8/T5 (35W up to 80W) fluorescent batten.
- Only 28W, 41W and 60W total load, up to 67% energy reduction vs traditional switch start.
- Over 110lm/W – exceeding building regulation requirements.
- 50 000 hour rated life, equivalent to 16 years at 12 hours per day, 5 days per week operation.

Construction

- Batten: pre-coated roll form steel, white (RAL9016).
- End caps/lamp holders: injection moulded polycarbonate, white.
- Diffuser: textured opal acrylic.

Installation

- Loop in/out 2.5mm² cables.
- Detachable LED engine for easy installation Ambient temperature: -20 to +25° Fixation to central BESA fixing or entrance through spine. Through wiring possible through knock out holes in the spine and end caps. Easy alignment through slots in the spine.
- Bare battens can be mounted end-to-end

Ordering Guide

Description	SAP Code
POPPACK LED 3000-840 L1200 HF PUK	96666172
POPPACK LED 4500-840 L1200 HF PUK	96666173
POPPACK LED 6500-840 L1500 HF PUK	96666174
POPPACK LED 4000-840 L1500 HF PUK	96666175

HF - High frequency electronic ballast

CONTACT DETAILS



5 Year Warranty

As a globally leading luminaire manufacturer, Thorn Lighting provides a five-year warranty for its complete product range.

www.thornlighting.com.au

THORN
LIGHTING PEOPLE