Urba

96269969 <URBA L 84L35 730 RWT BP CL2 T60E W10 AN

ISO 9223 C3 | IP66 | IK09

Urba

A large size LED urban street lighting lantern with 84 LEDs driven at 350mA with Wet Road optic. Electronic, fixed output control gear. Class II electrical, IP66, IK08. Body: die-cast aluminium, textured dark grey. Cover: tempered flat glass. Pre-wired with 10m cable. Post top mounting to Ø60mm column. Integral power reduction function which dims down to 50% power, effective 3 hours before and 5 hours after a calculated midnight. Complete with 3000K LED.

Dimensions: 1078 x 400 x 357 mm
Luminaire input power: 88 W
Weight: 17 kg
Scx: m²

TLG_URBA_F_LMTPGYPDB.jpg

This product contains light sources of energy efficiency class D.

All values marked with an * are rated values. Thorn uses tried and tested components from leading suppliers, however there may be isolated instances of technology-related failures of individual LEDs during the rated product lifetime. International standards set the tolerance in initial flux and connected load at ±10%. Unless stated otherwise, the values apply to an ambient temperature of 25°C.

Thorn Lighting is constantly developing and improving its products. The right is reserved to change specifications without prior notification or public announcement.
© Thorn Lighting