
Prisma


Slim LED luminaire with curved prismatic diffuser for surface mounting




- Through wiring (TW) variants available
- Robust and IP44 sealed housing extends applications to canteens, kitchens, laundry rooms, garages etc.
- Curved frosted (FR) prismatic diffuser for more visual comfort (wide light distribution, reduced glare)
- Highly efficient LED variants (up to 120 lm/W), sensor variants for even more energy saving
- Available in two lengths (600mm / 1200mm)

Photographs, line drawings and photometric data are representative only. For specific product detail please select an individual product.







96630837

Material/Finish

Body: Pre-painted white 0.7mm galvanised steel.
Endcaps: Shockproof ASA plastic, white.
Diffuser: Prismatic acrylic.

Installation/Mounting

Keyhole fixing positions Ø14mm for direct mounting to ceiling, wall or via bracket. Fixing centres: 500mm (600mm fixture). Two cable entries Ø19mm in the centre of the body and a knockout hole in the endcaps. Grommets included. Cable capacity 3 x 2 x 2.5mm².

Ordering Guide Lamps to be ordered separately, except where stated (L830/L840)

Description	ILCOS Code	Socket	Wt (kg)	SAP Code
Prisma				
PRISMA LED3000-840 HF FR L600	LED		1,502	96630824
PRISMA LED4400-840 HF FR L1200	LED		2,721	96630825
PRISMA LED6200-840 HF FR L1200	LED		2,721	96630826
PRISMA LED3000-830 HF FR L600	LED		1,502	96630830
PRISMA LED4400-830 HF FR L1200	LED		2,721	96630831
PRISMA LED6200-830 HF FR L1200	LED		2,721	96630832
Prisma, through wired				

IP44, Beam_Surface_3, IK06, Beam_eControl_A, SC1, Beam_Emergency, CE, T16, 650, 850

Thorn Lighting is constantly developing and improving its products. The right is reserved to change specifications without prior notification or public announcement.
© Thorn Lighting

Prisma

Description	ILCOS Code	Socket	Wt (kg)	SAP Code
PRISMA LED3000-840 HF FR L600 TW	LED		1,516	96630827
PRISMA LED4400-840 HF FR L1200 TW	LED		2,811	96630828
PRISMA LED6200-840 HF FR L1200 TW	LED		2,811	96630829
PRISMA LED3000-830 HF FR L600 TW	LED		1,516	96630833
PRISMA LED4400-830 HF FR L1200 TW	LED		2,811	96630834
PRISMA LED6200-830 HF FR L1200 TW	LED		2,811	96630835
Prisma, dimmable				
PRISMA LED3000-840 HFIX FR L600	LED		1,502	96630836
PRISMA LED4400-840 HFIX FR L1200	LED		2,721	96630837
PRISMA LED6200-840 HFIX FR L1200	LED		2,721	96630838
PRISMA LED3000-830 HFIX FR L600	LED		1,502	96630842
PRISMA LED4400-830 HFIX FR L1200	LED		2,721	96630843
PRISMA LED6200-830 HFIX FR L1200	LED		2,721	96630844
Prisma, dimmable, through wired				
PRISMA LED3000-840 HFIX FR L600 TW	LED		1,516	96630839
PRISMA LED4400-840 HFIX FR L1200 TW	LED		2,811	96630840
PRISMA LED6200-840 HFIX FR L1200 TW	LED		2,811	96630841
PRISMA LED3000-830 HFIX FR L600 TW	LED		1,516	96630845
PRISMA LED4400-830 HFIX FR L1200 TW	LED		2,811	96630846
PRISMA LED6200-830 HFIX FR L1200 TW	LED		2,811	96630847
Prisma, sensor versions				
PRISMA LED4400-830 HF FR MWS L1200	LED		2,735	96630848
PRISMA LED4400-840 HF FR MWS L1200	LED		2,735	96630849

Thorn Lighting is constantly developing and improving its products. The right is reserved to change specifications without prior notification or public announcement.
© Thorn Lighting