

Arrowslim T5

| | | |
|-------------|--------------------|--------|
| T16 (FDH) | G5 | 14-24W |
| AS/NZS60598 | Class I Electrical | |
| IP20 | | |

Arrowslim is a dedicated T5 (T16) fitting with single and twin lamp variants and enhanced appearance

- Single and twin lamp variants, extending application possibilities to include industrial, retail, commercial office and education lighting
- High frequency electronic ballasts, providing increased efficiency whilst eliminating flicker
- Three-position rotating lampholder provides maximum mounting flexibility for single lamp versions
- Available in both high output and high efficiency T5 (T16) lamps

Materials/Finish

Spine: steel, white enamel finish (RAL 9010)
Lampholder: polycarbonate, white finish


Installation/Mounting

Suitable for walls, ceilings or in cornice/pelmet areas. Three-position rotating lampholders allows lamp to be located either side of the spine.



Specification

To specify state:
Slim single or twin lamp fluorescent batten for 14/28W, T16 linear fluorescent lamps. As Thorn Arrowslim T5.



Single batten

Twin batten



| Wattage | Lengths |
|---------|---------|
| 14W | 572 |
| 28W | 1172 |

Ordering Guide Supplied complete with 840 lamp.

| Description | Ilcos Code | Socket | Wt (kg) | Cat. No. | SAP Code |
|---------------|------------|--------|---------|----------|----------|
| ARROSLM 1X14W | FD | G5 | 0.75 | AST5114 | 96211392 |
| ARROSLM 1X28W | FD | G5 | 1.1 | AST5128 | 96211396 |
| ARROSLM 2X14W | FD | G5 | 0.8 | AST5214 | 96211400 |
| ARROSLM 2X28W | FD | G5 | 1.2 | AST5228 | 96211404 |

