Avenue Deco Bollard

TC-D (FSQ)	G24d-3	26W
HME (QE)	E27	50W
AS/NZS 60598	Class I Electrical	
IK08/5Nm	IP54 (bollard)	

Elegant bollard, complementing the Avenue Deco lantern and column range

Design: Bjarne Frost and Peter Møller

- Bollard versions for flange, root or parapet mounting
- Variety of lamp types
- Characteristic cross design divides the light from the cone

Materials/Finish
Bollard: Top and column of cast/extruded aluminium, powder-coated anthracite.
Diffuser : Sandblasted polycarbonate.

Installation/Mounting
Root mounted version 450mm into the ground via ground spike to be ordered separately.
Flange mounted version uses bollard base as flange plate - fixes via four Ø10mm holes at 160mm x 160mm centres.
5 way terminal block for 6mm² conductors. Looping possible.
Integral control gear.

Specification
To specify state: Aluminium bollard for root/flange mounting with conical sandblasted diffuser employing 26W TC-D / 50W HME lamp.
As Thorn Avenue Deco.



Wall



Bollard Parapet



Ordering Guide Lamps to be ordered separately.

Description	Ilcos Code	Socket	Wt (kg)	Cat. No.	SAP Code
Bollard					
AVENUE BOL 26W TC-D LO 1M CL1 MPL ANT	FSQ	G24D-3	18.00	J129520	96004375
AVENUE BOL 50W HME CL1 1M/MPL ANT	QE	E27	17.30	J129544	96004377
Parapet					
AVENUE BOL 50W HME CL1 450MM MPL ANT	QE	E27	12.00	J129605	96100843
AVENUE BOL 26W TC-D 240V CL1 450MM MPL	FSQ	G24D-3	11.00	J129582	96101917
Wall Light complete with integral control gear					
AVENUE W400 26W TC-D CL1 LO ANT	FSQ	G24D-3	4.0	J133572	96004429
AVENUE W400 50W HME ANT	QE	E27	5.6	J133589	96004430
Attachment					
AVENUE/PROMENADE/MADISON BOL MGR SPIKE			10.00	J128196	96005367

Email Print Back X