

# Bornoval

HSE (SE)	E27	70W
AS/NZS 60598	Class II Electrical	
IK04/0.5 Nm (glass)	IK08/5 Nm (PC)	
IP55		

A bollard of striking design in heavy duty aluminium

- Two stainless steel straps in recessed channels running the full length retain the cap
- Oval cross-section with two lit faces
- Choice of vandal resistant glass lens optic or clear polycarbonate visor with louvre

### Materials/Finish

Body: Aluminium finished grey textured paint, with bright finish stainless steel side vertical straps.

Optics: Toughened soda lime moulded prismatic glass lens or white aluminium louvre with clear polycarbonate visor.

Gear tray: Removable aluminium tray.




### Installation/Mounting

250mm<sup>2</sup> flange plate with Ø18mm hole at each corner, at 200mm centres.

### Specification

To specify state: Oval cross section, aluminium, bollard with cap retaining stainless steel side bands. IP55 with prismatic glass/white louvre optical system housing removable gear tray for 70W HPS-E.

As Thorn Bornoval.



**Ordering Guide** Lamps to be ordered separately. For complete fitting order control gear and post.

Description	Ilcos Code	Socket	Wt (kg)	SAP Code
<b>210 control gears</b>				
BORNOVAL GT 70W HSE-E	SE	E27	1.76	96215786
<b>210 post without gear</b>				
BORNOVAL 210 EPR/GL GRY			10.20	96011224
BORNOVAL 210 ECL/PC GRY			10.20	96011226