

Bricklight

TC-S with G23 (2pin)	9W
AS/NZS 60598	Class II Electrical
IP34	

A recessed luminaire designed to replace a standard brick or for mounting inside a cavity wall

- Neutral colour to suit any environment
- Plain diffuser or louvre models
- Suitable for low level lighting application including corridors, hallways, path and steps

Materials/Finish

Body: moulded polycarbonate plastic.
 Diffuser: polycarbonate.
 Louvre: metal louvre, black
 Flush mounting trim: steel finished white.

Installation/Mounting

Recessed into the wall by use of flush mounting trim (cut-out 238 x 80mm).

Specification


To specify state:
 Purpose designed light fitting with IP34 rating. Designed to replace a standard brick or for recessing into a cavity wall. All moulded plastic body with integral LPF control equipment. One piece opal diffuser/black louvre/ luminaire. As Thorn Bricklight.



Opal diffuser



Black louvre



Ordering Guide Supplied complete with lamp. For complete fitting order luminaire and housing.

Description	Ilcos Code	Socket	Wt (kg)	Cat. No.	SAP Code
BRICKLIGHT OPAL TC-SEL 1 X 9W	FSD	2G7	1.3	BT09	96017248
BRICKLIGHT LOUVRE TC-SEL 1 X 9W	FSD	2G7	1.3	BTL9	96017249
Housing					
FLUSH MOUNTING TRIM				FMT	96016586



Arachon, Wine Cellar, Austria