

# Guardian Bulkhead S

TC-TEL (FSQ) G24q-1 13W  
AS/NZS60598 Class I Electrical

Wall and ceiling mounted energy efficient luminaire with simple construction

- High frequency electronic control gear
- Energy efficient 13WTC-DEL compact lamp supplied with luminaire
- Tough injection moulded prismatic UV resistant polycarbonate diffuser
- Close ceiling or wall mount resists prising from surface improving vandal resistance
- Stainless steel security screws

## Materials/Finish



Body: 1.6mm Mild steel; Electro Plated (ZN10) protection prior to white powder coat finish.  
Diffuser: Injection moulded UV resistant prismatic polycarbonate.  
Security screws: Stainless steel.

## Installation/Mounting

Wall or ceiling mounted via 4 x 4.5mm fixing holes. Cable access via 25mm cable entry hole, geometrically centred. Diffuser held by 4 x M4 stainless steel security screws.

## Specification

To specify state: Rectangular surface luminaire with a prismatic polycarbonate diffuser, integral high frequency electronic warm start control gear and lamp.  
As Thorn Guardian Bulkhead S.



**Ordering Guide** Supplied complete with lamp.

Description	Ilcos Code	Socket	Wt (kg)	Cat. No.	SAP Code
<b>Bulkhead GUSBH</b>					
GUARDIAN BULKHEAD S 1X13W HF	FSQ	G24q-1	1.00	GUSBH113	96039344