

T26 (FD)	G13	18W
AS/NZS 60598	Class I Electrical	
IP54		

A corrosion resistant fully moulded fluorescent light fitting. Designed for use in a wide range of arduous conditions

- Suitable for humid and corrosive atmospheres, chemical processing plants, laundries and exterior applications
- IP54 protection rating
- Choice of clear or opal diffuser
- Corrosion resistant body
- Vandal resistant construction

Materials/Finish

Body and gear tray: glass filled nylon (GRP) grey (body) and white (gear tray).
Diffuser: impact resistant acrylic clear or opal.
Gasket: continuous solid neoprene.
Corrosion resistant plated hardware.

Installation/Mounting

Suitable for ceiling or wall mounting. 20mm conduit entry at each end. Alternate cable entry through boss in top of body.

Specification



To specify state:
A corrosion resistant IP54 fluorescent fitting with GRP body for T26 lamps, with clear or opal diffuser.
As Thorn Casalux.



Opal diffuser



Callide, Gladstone, QLD



Ordering Guide

Supplied complete with lamps.

Description	Ilcos Code	Socket	Wt (kg)	Cat. No.	SAP Code
Clear diffuser					
CASALUX T26 1X18W	FD	G13	3	CASC118H	96015567
Opal diffuser					
CASALUX T26 1X18W	FD	G13	3	CASO118H	96015572