

# Chameleon T5

T16 (FD)	G5	14-28W
AS/NZS60598	⊕ Class I Electrical	
IP20/IP54		

The Chameleon series is a complete range of luminaires for most recessed applications

- Option of 1200 x 300, 1200 x 600, 600 x 300 and 600 x 600 for T-bar or plaster ceiling
- Flush fit prismatic diffuser frame with torsion spring (IP20)
- IP20 or IP54 versions
- K12 diffusers
- Dimming versions on request
- Other diffusers available to special order
- IP54 versions with security frame options
- Return air versions available to special order



## Material/Finish



Body: steel, white painted.  
Reflector: steel, white painted inside reflector.  
Diffuser: acrylic K12.

## Installation/Mounting

Suitable for standard 1200 x 300, 1200 x 600, 600 x 300 and 600 x 600 T-bar grid and plaster ceiling.

## Specification

To specify state:  
Recessed fluorescent luminaire with HF control gear to suit 1200 x 300, 1200 x 600, 600 x 300, 600 x 600 exposed T-bar or plaster ceiling for 14/28W T16 lamps.  
As Thorn Chameleon T5.



**Ordering Guide** Supplied complete with lamps (840) and K12 diffuser.

Description	Ilcos Code	Socket	Wt (Kg)	Old Cat Code	SAP Code
<b>IP20</b>					
CHAMELEON 2X14W T16 HF 600X300 I1840	FD	G5	5.40	CTN214TSELEC	96038466
CHAMELEON 3X14W T16 HF 600X600 I1840	FD	G5	6.00	CTW314TSELEC	96038467
CHAMELEON 4X14W T16 HF 600X600 I1840	FD	G5	6.00	CTW414TSELEC	96038468
CHAMELEON 2X28W T16 HF 1200X300 I1840	FD	G5	6.80	CTN228TSELEC	96038469
CHAMELEON 3X28W T16 HF 1200X600 I1840	FD	G5	7.30	CTW328TSELEC	96038470
<b>IP54</b>					
CHAMELEON IP 2X14W T16 HF 600X300 I1840	FD	G5	5.40	CTNIP214TSELEC	96038484
CHAMELEON IP 3X14W T16 HF 600X600 I1840	FD	G5	6.00	CTWIP314TSELEC	96038486
CHAMELEON IP 4X14W T16 HF 600X600 I1840	FD	G5	6.00	CTWIP414TSELEC	96038487
CHAMELEON IP 2X28W T16 HF 1200X300 I1840	FD	G5	6.80	CTNIP228TSELEC	96038488
CHAMELEON IP 3X28W T16 HF 1200X600 I1840	FD	G5	7.30	CTNIP328TSELEC	96038489