

# Corniche

T16 (FD)	G5	24-39W
AS/NZS 60598	Class II Electrical	
IP65		

Slim linear T16 luminaire providing 'close off-set' facade illumination with good uniformity

- Ideal for providing a broad band of even illumination on a surface from a close mounting position
- Built in thermal protection device maintains lamp operating temperature for optimum output
- Neat profile enables unobtrusive installation
- Supplied with high output T16 fluorescent lamps, operating from electronic control gear.
- Available in 2 lengths: 617mm (24W) and 917mm (39W)
- Choice of asymmetric or symmetric reflectors
- Extruded aluminium body and aluminium end caps

## Materials/Finish




Body: extruded aluminium, finished in powder coated polyester paint.  
 End caps: aluminium, finished in powder coated polyester paint.  
 Brackets: galvanised steel, finished in powder coated polyester paint.  
 Lens: polycarbonate sealed by neoprene gasket.  
 Faceted reflector: banded aluminium.  
 Screws: stainless steel. RAL colours available on request.

## Installation/Mounting

Supplied with a pre-wired 1.0m length of cable (3 x 1.0mm<sup>2</sup>) with a connected IP54 rated Wieland plug (4Kv/3 VDE 0110/01.89). Terminal block capacity of Wieland plug: 3 x 2.5mm<sup>2</sup>. Access to lamp and control gear gained by removing front lens. The projector is supplied with two versatile brackets which can be slid along the length of the extrusion so that a variety of different fixing points are available. These brackets provide easy installation and maintenance on uneven surfaces.

## Specification

To specify state: Wall washing linear floodlight for 24/39W T16 linear fluorescent lamps with symmetric/asymmetric light distribution and glass/polycarbonate enclosure. Sealed to IP65. As Thorn Corniche.



## Ordering Guide

Supplied complete with lamp.

Description	Icos Code	Socket	Wt (kg)	Cat. No.	SAP Code
<b>Polycarbonate</b>					
CORNICHE 39W T16/LI/830 E/PC A/S	FDH	G5	4.60	CCT5393KAR.4	96010445
CORNICHE 24W T16/LI/830 E/PC S/S	FDH	G5	3.20	CCT5243KSR.4	96010440
CORNICHE 39W T16/LI/830 E/PC S/S	FDH	G5	4.60	CCT539KSR.4	96010442
CORNICHE 24W T16/LI/830 E/PC A/S	FDH	G5	3.20	CCT5243KAR.4	96010444
<b>Accessories</b>					
CORNICHE KIT HOOK FIX			0.80	CCTBKT	96012339

PC - Polycarbonate S/S - Symmetric A/S - Asymmetric