

Dragon

	TC-S (FSD)	G23	3000K	11W
	TC-L (FSD)	2G11	4000K	18W
AS/NZS 60598				
	Class I Electrical			IK09/10Nm
	IP65			

A robust bulkhead using low energy fluorescent lamps with the emphasis on a smooth appearance. The construction is simple with a high degree of engineering and special attention has been paid to maintenance and safety aspects

- Strong die cast aluminium body with rounded profile
- Clear polycarbonate diffuser fixes via two cross head screws
- IP65 rated, with silicone gasket seal
- Gloss white stove enamelled gear-tray doubles as reflector
- Double pole automatic isolation
- 3 pole terminal block with built-in fuse
- Threaded holes with white cap for 20mm side entry



Materials/Finish


Body: die-cast aluminium, painted white with gloss white stove enamelled gear-tray.
Stainless steel lamp support
Diffuser: clear UV stabilised prismatic polycarbonate.

Installation/Mounting

Direct wall or ceiling mounting. 4 fixing points. Knockouts and pre-drilling points for BESA box fixing. Threaded holes with white cap for 20mm side entry through wiring. Hinged gear-tray provides quick access to 3 pole terminal block with built-in fuse. Double pole automatic isolation. Gear-tray secures with single screw.
Safety-cord between body and diffuser.

Specification

To specify state:
IP65 vandal resistant bulkhead for 2X11W TC-S and 1X18W TC-L compact fluorescent lamps with die-cast aluminium body and clear polycarbonate diffuser, internal fuse and automatic disconnection plus diffuser retaining safety cord.
As Thorn Dragon.



Ordering Guide

Description	Ilcos Code	Socket	Wt (kg)	Sap code	Old Cat. No.
DRAGON 1X18W TC L HF U840	FSD	2G11	1.1	96230475	OBDZ1018
DRAGON 2X11W TC S U830	FSD	G23	1.1	96230476	OBD2011-4

