










Gamma Basique

 HST (ST)	E27/E40	70-100W
 HSE (SE)	E27/E40	70-100W
 HIT-CE (MT)	E27	70W
AS/NZS 60598  Class I Electrical		
5 Nm Impact resistant		
40 Nm Impact resistant vandal resistant version		
 IP65		

A 'best value' post-top amenity lantern range

- Ideal for precincts, car parks, approach roads and pedestrian areas
- Choice of lamps including 'white light' options to suit differing applications
- Small or large canopy to suit given environment
- Clear or opal reeded bowl for improved aesthetics

- Vandal resistant version for high risk areas - delivered fully assembled. 40 Nm impact resistance 
- Refractor versions for asymmetric light distribution - controls/directs light and reduces light spill
- Miniature electronic photocell versions for automatic on/off switching
- Quick and easy installation with hinged gear tray
- Environmentally friendly - material fully recyclable



Hinged gear tray

Materials/Finish

Bowl/Diffuser: injection moulded 5 Nm acrylic (vandal resistant version - polycarbonate) opal reeded or clear reeded finish (vandal resistant version - clear reeded only).

Base: die-cast aluminium, dark grey powder coat textured finish, close to RAL 7010.

Canopy: spun aluminium, dark grey powder coat finish with white underside.

Installation/Mounting

Post top mounting - 76mm diameter x 76mm long spigot. (Dedicated accessory available to allow 60mm diameter x 100 long spigot mounting).

Recommended mounting height: 4 to 5 metres. Fixes to shaft with 3 x M8 stainless steel screws (supplied). Vandal proof version supplied fully assembled, complete with clear reeded bowl and small canopy.

Specification

To specify state:

Amenity post top lantern made with die-cast aluminium base in grey power coat, 5 Nm acrylic opal/clear reeded bowl/diffuser and canopy in spun aluminium with dark grey powder coat. As Thorn Gamma Basique.



FR © GPO

Ordering Guide Lamp to be ordered separately. For complete fitting please order base assembly with gear, bowl/diffuser and canopy.

Description	Ilcos Code	Socket	Wt (kg)	Cat. No.	SAP Code
Base assemblies with gear					
HST/HSE/HIT-CE 70W	SE/ST/MT	E27	3.4	QGB70HPS/CDM-TT.4	96008280
HST/HSE 100W	SE/ST	E40	3.6	QGB100HPS.4	96008287
HST/HSE/HIT-CE WITH REFRACTOR 70W	SE/ST/MT	E27	4.1	QGB70HPS/CDM-TT.4REF	96008583
Bowls/Diffuser					
GAMMA B CLEAR REEDED ACRYLIC BOWL			1.0	QGBCBAC	96008257
GAMMA B OPAL REEDED ACRYLIC BOWL			1.0	QGBOBAC	96008258
Canopies					
GAMMA LARGE CANOPY			1.3	QGBCANOPYL	96008288
GAMMA LARGE CANOPY WITH MINIATURE PHOTOCELL			1.3	QGBCANOPYLPM	96008292
GAMMA SMALL CANOPY			1.0	QGBCANOPYS	96008286
GAMMA SMALL CANOPY WITH MINIATURE PHOTOCELL			1.0	QGBCANOPYSPM	96008277
Vandal resistant*					
GAMMA B 70W HST/HSE/HIT-CE + PHOTOCELL	SE/ST/MT	E27	5.2	QGV70HPS/CDM-TT.4P	96011999
GAMMA B 70W HST/HSE/HIT-CE	SE/ST/MT	E27	5.2	QGV70HPS/CDM-TT	96012000

*This product is delivered fully assembled, complete with clear reeded polycarbonate bowl/diffuser and small canopy.



NSW Rural Fire HQ, Rosehill, NSW