


T16 (FDH)	G5	24-28W
TC-L (FSD)	2G11	40W
AS/NZS60598		
Class I Electrical		
IP20		

Attractive range of recessed mellowlight luminaires for T16 (T5) or TC-L fluorescent lamps with unique aesthetics. Offers excellent lighting performance and enhances lit environment with direct and indirect light

- The stylish Menlosoft range offers excellent lighting performance and enhances the lit environment with attractive designs and ambient, mellow light
- Menlosoft makes a striking feature in all types of office applications, retail environments and circulation routes
- Available in two different size options to suit different ceilings: 600x600mm and 300x1200mm
- A combination of direct and indirect light provides a warm glow to all application areas
- Low maintenance (tool free lamp replacement)



Organic attachment




Cut out:
576 x 576
1176 x 276

Prismtech attachment



Perforated with opal diffuser



Mirrorbrite DMB louvre

Slotted with DSB louvre

Materials/Finish

Body and reflectors: white painted steel.

Opal Diffuser: white stove enamelled steel, opal polycarbonate.

Prismtech attachment: white lacquered steel frame, polycarbonate prismatic panel.

Organic attachment: white lacquered steel with slots.

Louvre attachment: white lacquered steel with perforations or slots and central aluminium louvre in Satinbrite (semi-specular) finish.

Installation/Mounting

Suitable for most 15mm or 24mm exposed tee ceilings, the luminaire simply lays onto the ceiling grid for quick installation. For installation from below into concealed fixed and plasterboard ceilings, use wedge brackets (supplied). Attachments are hinged on one side with unique magnetic fixing for ease of maintenance. Electrical connection via piano key terminal block.

Specification

To specify state: Unique aesthetic recessed luminaire with direct/indirect lighting performance for 24-28W T16 (T5) linear fluorescent or 40W TC-L compact fluorescent lamps with louvre, diffuser or solid optic attachments. Suitable for lay-in into exposed tee grids or for concealed fixed or plasterboard ceilings with unique "wedge" bracket.

As Thorn MenloSoft.

Ordering Guide Supplied complete with lamps. For complete fitting order body and attachment.

Description	Ilcos Code	Socket	Wt (kg)	Cat. No.	SAP Code
600 x 600 Body					
MENLOSFT BODY 2X24W T16 HF 600	FDH	G5	4.1	MENLO224HF	96200520
MENLOSFT BODY 2X40W TC-L HF 600	FSD	2G11	4.2	MENLO240HF	96230422
MENLOSFT BODY 3X24W T16 HF 600	FDH	G5	4.3	MENLO324HF	96200529
300 x 1200 Body					
MENLOSFT BODY 2X28W T16 HF 300X1200	FDH	G5	4.3	MENLO228HF	96200501

Dimming versions available to special order

Description	Wt (kg)	Cat. No.	SAP Code
Attachments for 600x600 module body			
MENLOSFT OPAL MP 600X600MM	1.3	MENLOWC2606	96008856
MENLOSFT OPAL SL 600X600MM	1.4	MENLOWC4606	96008859
MENLOSFT LOUVRE MP DMB 600X600MM	1.4	MENLOWC2606MB	96008864
MENLOSFT LOUVRE MP DSB 600X600MM	1.3	MENLOWC2606SB	96008867
MENLOSFT LOUVRE SL DMB 600X600MM	1.4	MENLOWC4606MB	96008870
MENLOSFT LOUVRE SL DSB 600X600MM	1.4	MENLOWC4606SB	96008873
MENLOSFT PRISMTEC 600X600MM*	1.4	MENLOPT606	96008875
MENLOSFT ORGANIC 600X600MM	1.3	MENLODF606	96008879
Attachments for 300x1200 module body			
MENLOSFT PRISMTEC 1200X300MM	1.2	MENLOPT312	96008877
MENLOSFT ORGANIC 1200X300MM*	1.4	MENLODF312	96008881

MP - Microperforated diffuser, SL - Slotted diffuser, DMB - Mirrorbrite louvre, DSB - Satinbrite louvre
*Supplied complete with white (x2) decorprisms

