

MenloSoft Circular

T16R (FSCH)	2GX13	55W
AS/NZS60598	⊕ Class I Electrical	
IP40		

Eye catching circular design combined with gentle light for modern office architecture



Materials/finish

Body: mild steel, powder coated white.
Reflector: deep drawn steel, powder coated white.
Attachment: steel plate, powder coated white.
Diffuser: opal polycarbonate (mounted inside the attachment).

Installation/Mounting

Suitable for exposed tee grids and concealed fix or plasterboard mounting. The attachment twists open for access to the lamp. Electrical connection via 3 x 2.5mm² terminal block with looping facility. Easy installation with our unique 'Wedge' bracket fixing.

Specification

To specify state:
Eye catching circular recessed modular luminaire for 55W T16-R circular fluorescent lamps with centrally mounted circular attachment and diffuser, with unique 'wedge' bracket fixing. As Thorn MenloSoft Circular.

- The modular body has a centrally mounted, circular attachment with slotted perforations, designed for T5-C (T16-R) circular lamps
- Unique 'Wedge' bracket fixing (included) for easy installation
- Low maintenance (tool free lamp replacement)
- Slender and shallow design (90mm depth)





Ordering Guide

Lamps to be ordered separately.

Description	Icos Code	Socket	Wt (kg)	SAP Code
MENLOSOFT CIRC 1X55W T16-R HF 596	FSC	2GX13	6.3	96013116

Dimming versions available to special order



Thorn Lighting, Head Office, Herefordshire, UK