

Munaline

MHN-LA (MD)	2kW
AS/NZS 60598	Class I Electrical
IP65	

Specifically designed to handle operating conditions on draglines, with reinforced mounting assembly to withstand high vibration and mechanical forces

- High lighting performance
- Variable lampholder positions
- Easy installation and maintenance with rear access

Materials/Finish


Body and frame: die-cast aluminium.
 Front glass: thermal resistant 4mm clear glass.
 Stirrup: unpainted galvanised steel.

Installation/Mounting

Stirrup fixed by single M20 bolt through Ø22mm central hole, or twin bolts through Ø15mm holes.
 Cable clamp supplied for Ø7.5-13mm flexible cable.
 Ignitor mounted on floodlight.
 Ballast and capacitors to be selected and mounted remotely.
 Hood accessory fixes via 4 screws.

Specification

To specify state:
 Dragline floodlight 2/kW linear metal halide lamps, in die-cast aluminium rear access to the lamp. IP65.
 Class I insulation.
 As Thorn Munaline.



Ordering Guide Lamps to be ordered separately. For complete fitting please order floodlight and gear tray.

Description	Ilcos Code	Socket	Wt (kg)	Cat. No.	SAP Code
Floodlight					
MUNALINE 2KW MHNLA	MD	-	14.5	MUNA3LINE	96034917
Gear Tray					
CG TM 2KW MHNLA 415V NI FUSED				CGTM2MHNLA415NIF	96038307
CG WP 2KW MHNLA 415V NI FUSED				CGWP2MHNLA415NIF	96038308

TM - Tray mounted, WP - Weatherproof, NI - No ignitor.