

PowerForce

T26 (FD)	G13	18-58W
AS/NZS 60598	Class I Electrical	
IP54 (below)		

Rugged construction makes this heavy duty light fitting particularly suitable where tough, arduous or dirty environments are experienced

- Suitable for general industrial interiors and exteriors, power stations, foundries, heavy plant locations, machine shops, coal handling plants, mining applications
- IP54 protection rating
- Fused terminal block
- HPF control gear
- Positive lock rotary tombstone lampholders
- Maintenance safety lanyards on lens and gear tray
- Key hole mounted gear tray

Materials/Finish

Body: extruded aluminium
End plates: die-cast aluminium.
Diffuser: clear polycarbonate.
Toggles: stainless steel (PowerForce extra).

Installation/Mounting


Direct on surface utilising supplied mounting hardware in continuous slots.
Chain mounting via optional mounting kit supplied separately.

Specification

To specify state:
IP54 rated dust and moisture resistant fluorescent fitting. Fitted with warm start high frequency ballast/switchstart gear to operate T26 lamp(s).
As Thorn PowerForce.



PowerForce



Callide, Gladstone, QLD

Ordering Guide

Supplied complete with lamp.

Description	Ilcos Code	Socket	Wt (kg)	Cat. No.	SAP Code
PowerForce					
POWERFORCE T26 1X18W	FD	G13	4.5	PWR118H	96016976
POWERFORCE T26 2X18W	FD	G13	10	PWR218H	96016982
POWERFORCE T26 1X36W	FD	G13	4.5	PWR136H	96016978
POWERFORCE T26 2X36W	FD	G13	10	PWR236H	96016985
POWERFORCE T26 1X58W	FD	G13	4.5	PWR158H	96016980
POWERFORCE T26 2X58W	FD	G13	10	PWR258H	96016987
PowerForce Extra					
POWERFORCE EXTRA T26 1X18W	FD	G13	4.5	PWR118H	96016993
POWERFORCE EXTRA T26 2X18W	FD	G13	10	PWR218H	96016995
POWERFORCE EXTRA T26 1X36W	FD	G13	4.5	PWR136H	96038512
POWERFORCE EXTRA T26 2X36W	FD	G13	10	PWR236H	96016996
POWERFORCE EXTRA T26 1X58W	FD	G13	4.5	PWR158H	96016994
POWERFORCE EXTRA T26 2X58W	FD	G13	10	PWR258H	96016998
Accessory					
MOUNT ASSEMBLY (SET OF 2)				PWRMTG	96017002