

Sonpak LX 7

	HSE-I (SE)	E27	70W
	HIT-DE (DE)	RX7s	70W
AS/NZS 60598		Class I Electrical	
5 Nm Impact resistant		IP65	

A new range of easy to install performance floodlights supplied complete with lamp



- Asymmetric or symmetrical reflector
- Easy to install with drop down front glass and cable entry
- Tough, polypropylene body
- Vandal resistant construction with high impact clear polycarbonate visor
- Integral control gear
- Sealed to IP65

Materials/Finish

Body: polypropylene, black colour, reinforced with fibreglass and mineral loads.

Diffuser/lens : self-extinguishing polycarbonate.

Reflector: Hammered aluminium sheet P-AL 99,85% alloy 1060, polished, oxidized and anodised, suitable thickness.

Screws: Chrome-galvanised steel.

Cable gland: M20 cable gland Ø9-11mm. Gasket: anti-ageing rubber.


Terminal block: Screw type connection terminal, terminal section 4.0mm².

Fixing of supply cable: plastic clamp for cables diameter 9-11mm.

Bracket: Steel finished in black (RAL 9005), can be fixed through M6 screws, supplied with graduated scale for floodlight aiming.



Louvre



Visor



Installation/Mounting

All products have one cable glanded entry for Ø9-11mm cable with 3 pole terminal blocks. LX7 stirrup fixed by single bolt through Ø16mm hole. Two additional Ø11mm fixing holes at 100mm centres, with a further two Ø13mm fixing holes at 180mm centres.

Specification

To specify state: Enclosed black polypropylene floodlight with polycarbonate visor, integral control gear, asymmetrical and symmetrical reflectors for 70W HIT and HSE-I lamps. Sealed to IP65.

As Thorn Sonpak LX7.



Ordering Guide

Description	Icos Code	Socket	Wt (kg)	Cat. No.	SAP Code
Sonpak LX 7					
SONPAK LX 70W 240V HSE-I/E27/220 A/S	SE/I	E27	3.40	OTX70	96232640
SONPAK LX 70W 240V HIT-DE/RX7S/730 A/S	MD	RX7S	3.40	OTXMH70	96232642
Attachments and Accessories					
SONPAK LX 70W LV	LOUVRE		1.00	OTX70L	96250690
SONPAK LX 70W VS	VISOR		1.00	OTX70V	96250691
SONPAK LX MA 76	SPIGOT		2.00	OTX76S	96250695