

Stradalux

T26 (FD)	G13	18W
AS/NZS 60598	Class I Electrical	
IP54		

A robust weatherproof general purpose fluorescent light fitting designed to meet a range of industrial and commercial lighting needs

- Suitable for minor streets, walkways, tunnels and marine applications
- Robust body
- Optional polycarbonate visor
- Individual ballast lamps
- Side and top entry models
- High light output
- Low maintenance
- Special vibration and wind resistant lamp holders



Materials/Finish

Body: die-cast aluminium.
Visor: high impact resistant clear acrylic (polycarbonate visor available on request).
Gasket: PVC foam.

Installation/Mounting

Optional multi-mounting bracket suits wall, corner and pole mounting situations.
25mm spigot and end cable entry standard.
20mm tapped top entry and suspension hole available.



Specification

To specify state:
Aluminium IP54 weatherproof fitting for 18W T26 linear fluorescent lamps for wall, corner or post top mounting.
As Thorn Stradalux.

Ordering Guide

Lamps to be ordered separately.

Description	Ilcos Code	Socket	Wt (kg)	Cat. No.	SAP Code
STRADALUX T26 2 X 18W HPF END ENTRY	FD	G13	3.5	STR218E1H	96019481
STRADALUX T26 2 X 18W HPF TOP ENTRY	FD	G13	3.5	STR218T1H	96019499
Emergency versions					
STRADALUX T26 2 X 18W HPF END ENTRY	FD	G13	3.5	STR218EH5XX00	96019491
Accessory					
STRADALUX MULTI-MOUNT BRACKET				SLBKT	96028009
STRADALUX CORNER BRACKET					96032148



Multi-mounting bracket accessory

