

Guardian Surface Mount

FT26 (FD)	G13	36W
AS/NZS60598	⊕ Class I Electrical	

A surface fluorescent luminaire with robust construction designed for high security applications

- Integral HF control gear
- Integral emergency options (EM)
- Twin circuits or (EM)/UPS option
- Diffuser slides out (EA version only) Note: suitable space required for accessibility
- Stainless steel security screws
- Internally fused
- Security or pop rivet access prevention - (EA version only)
- No cable entry
- Quick release drop down removable gear

Materials/Finish



Body & Frame: Manufactured from 1.6mm mild steel with a white powder coat finish. Diffuser: 4.5mm stippled polycarbonate. Screws: M6 countersunk stainless steel security type, to specification. Pop rivets: Alternative to security screws and available for EA versions only.

Installation/Mounting

Surface mounting nominal sizes 1200x200

Specification

To specify state: Surface mounted security luminaire single/twin 36W tubes with HF electronic control gear and 4.5mm stippled polycarbonate diffuser. As Thorn Guardian Surface Mount.



Ordering Guide Supplied complete with lamp.

Description	Ilcos Code	Socket	Wt (kg)	Cat. No.	SAP Code
Surface Prismatic					
GUARDIAN SURFACE 2X36W HF	FD	GR13	11.00	GU236	96039349
GUARDIAN SURFACE END ACCESS 2X36W HF	FD	GR13	11.00	GU236/EA	96039350