

Guardian Wall Mount

TC-D (FSQ) G24d-1 13W
AS/NZS60598 Class I Electrical

For high abuse areas, a secure light fitting designed to prevent access to the luminaire

- Manufactured from 1.6mm sheet steel for strength and a high reflective powder coat finish
- Vandal resistant 4.5mm stippled polycarbonate diffuser
- Integral switch start (B1) LPF control gear
- Energy efficient compact fluorescent lamp
- Suitable as a reading light
- Close wall mount resists prising from surface improving vandal resistance



Materials/Finish

Body: 1.6mm sheet steel with high reflective powder coat finish.

Diffuser: 4.5mm stippled polycarbonate.

Security screws: Stainless steel.


Installation/Mounting

Surface, wall mounting via 2 x 6mm fixing holes. Cable access to the fused terminal block via 25mm cable entry hole, geometrically centred.

Specification

To specify state: Wall mounted inclined high abuse luminaire with security screws, stippled polycarbonate lens integral control gear and 13W TC-D lamp.

As Thorn Guardian Wall Mount.



Ordering Guide Supplied complete with lamp.

Description	Ilcos Code	Socket	Wt (kg)	Cat. No.	SAP Code
Wall Mount					
GUARDIAN WALL MOUNT 1X13W	FSQ	G24d-1	2.55	GU113	96039343