

# Urba

# THORN

96269965 URBA L 72L70V2 NR ANT BP C2 10MMTP6 730

IP66	IK09		
------	------	---	---

## Urba

A large size LED urban street lighting lantern with 72 LEDs driven at 700mA with Narrow Road optic. Electronic, fixed output control gear. Class II electrical, IP66, IK08. Body: die-cast aluminium, textured dark grey. Cover: tempered flat glass. Pre-wired with 10m cable. Post top mounting to Ø60mm column. Complete with 3000K LED.

Dimensions: 1078 x 400 x 357 mm

Total power: 153 W

Weight: 17 kg

Scx: m<sup>2</sup>



TLG\_URBA\_F\_LMTPGYPDB.jpg

All values marked with an \* are rated values. Thorn uses tried and tested components from leading suppliers, however there may be isolated instances of technology-related failures of individual LEDs during the rated product lifetime. International standards set the tolerance in initial flux and connected load at ±10%. Colour temperature is subject to a tolerance of up to +/-150 Kelvin from the nominal value. Unless stated otherwise, the values apply to an ambient temperature of 25°C.

In most products the failure of one LED point causes no functional impairment to the lighting performance of the luminaire and is therefore no reason for complaint. Unless otherwise stated all Thorn LED products are suitable for unrestricted use (rated RG0 or RG1) with regard photobiological blue light safety (IEC/EN60598-1).

Thorn Lighting is constantly developing and improving its products. The right is reserved to change specifications without prior notification or public announcement.  
© Thorn Lighting

**Urba**

**96269965 URBA L 72L70V2 NR ANT BP C2 10MMTP6 730**

**THORN**