Graffiti

96108760 GRAFFITI 2800-940HE SWI 3GU FL BK



Graffiti

LED spotlight for 3 phase track installations with flood light distribution and stabilized color temperature.. Class I electrical, IP20. Body: die-cast aluminium black micro-textured paint. Reflector: PC sputtered. Spotlight rotatable through 337° and pivotable through 90°. Complete with 4000K LED, maximum efficiency


This article is single packed article and can also be ordered bulk packed.

Dimensions: Ø95 x 205 mm Luminaire input power: 21 W Luminaire luminous flux: 2800 lm Luminaire efficacy: 133 lm/W Weight: 0.71 kg



|H()

TLG_GRAF_F_3GU_BK_ON.jpg



TLG_GRAF_M_3GU.wmf

This product contains a light source of energy efficiency class C.

All values marked with an * are rated values. Thorn uses tried and tested components from leading suppliers, however there may be isolated instances of technology-related failures of individual LEDs during the rated product lifetime. International standards set the tolerance in initial flux and connected load at ±10%. Unless stated otherwise, the values apply to an ambient temperature of 25°C.

Thorn Lighting is constantly developing and improving its products. The right is reserved to change specifications without prior notification or public announcement. © Thorn Lighting

Graffiti

96108760 GRAFFITI 2800-940HE SWI 3GU FL BK

THORN