

# R2L2

# THORN

96266214 R2L2 S 36L70 730 WSC CL2 GY

ISO 9223 C5	ida BLACK SKY APPROVED	IP66	IK08					T <sub>a</sub> -25 +35
----------------	---------------------------	------	------	--	--	--	--	---------------------------

## R2L2

A small size LED road lighting lantern with 36 LEDs driven at 700mA with Wide Street & Comfort optic. LED driver Programmable. Class II electrical, IP66, IK08. Housing: die-cast aluminium (EN AC-44300), powder coated textured light grey. Enclosure: tempered flat glass. Screws: stainless steel, Ecolubric® treated. Post top (Ø60/76mm, tilted 0°/5°/10°) or lateral (Ø34/42/49/60mm, tilted 0°/-5°/-10°/-15°) mounting. For lateral mounting to Ø34/42mm spigots an adaptor (59005840 R2L2 MA34/42 NPA) should be ordered separately. Complete with 3000K LED.

Dimensions: 655 x 362 x 155 mm

Luminaire input power: 78 W

Luminaire luminous flux: 10041 lm

Luminaire efficacy: 129 lm/W

Weight: 9.32 kg

Scx: 0.05 m<sup>2</sup>



TLG\_R2L2\_F\_SPDB.jpg



TLG\_R2L2\_M\_LDS.wmf

This product contains a light source of energy efficiency class D.

All values marked with an \* are rated values. Thorn uses tried and tested components from leading suppliers, however there may be isolated instances of technology-related failures of individual LEDs during the rated product lifetime. International standards set the tolerance in initial flux and connected load at ±10%. Unless stated otherwise, the values apply to an ambient temperature of 25°C.

Thorn Lighting is constantly developing and improving its products. The right is reserved to change specifications without prior notification or public announcement.  
© Thorn Lighting