

## R2L2

THORN

96265920 R2L2 S 12L50 730 WSC BS 3550 CL2 GY

|          |     |      |      |  |  |  |  |  |  |                           |
|----------|-----|------|------|--|--|--|--|--|--|---------------------------|
| ISO 9223 | ida | IP66 | IK08 |  |  |  |  |  |  | T <sub>a</sub> -25<br>+50 |
| C5       |     |      |      |  |  |  |  |  |  |                           |

### R2L2

A small size LED road lighting lantern with 12 LEDs driven at 500mA with Wide Street & Comfort optic. LED driver Programmable. Class II electrical, IP66, IK08. Housing: die-cast aluminium (EN AC-44300), powder coated textured light grey. Enclosure: tempered flat glass. Screws: stainless steel, Ecolubric® treated. Post top (Ø60/76mm, tilted 0°/5°/10°) or lateral (Ø34/42/49/60mm, tilted 0°/-5°/-10°/-15°) mounting. For lateral mounting to Ø34/42mm spigots an adaptor (59005840 R2L2 MA34/42 NPA) should be ordered separately. Equipped with 50% power reduction circuit, effective 3 hours before and 5 hours after a calculated midnight. It can be deactivated at installation with an easily accessible internal switch. Complete with 3000K LED.

Dimensions: 655 x 362 x 155 mm

Luminaire input power: 20 W

Luminaire luminous flux: 2522 lm

Luminaire efficacy: 126 lm/W

Weight: 8.89 kg

Scx: 0.05 m²



TLG\_R2L2\_F\_SPDB.jpg



TLG\_R2L2\_M\_LDS.wmf

This product contains a light source of energy efficiency class D.

All values marked with an \* are rated values. Thorn uses tried and tested components from leading suppliers, however there may be isolated instances of technology-related failures of individual LEDs during the rated product lifetime. International standards set the tolerance in initial flux and connected load at  $\pm 10\%$ . Unless stated otherwise, the values apply to an ambient temperature of 25°C.

Thorn Lighting is constantly developing and improving its products. The right is reserved to change specifications without prior notification or public announcement.  
© Thorn Lighting

**R2L2**

**96265920 R2L2 S 12L50 730 WSC BS 3550 CL2 GY**

**THORN**