

## R2L2

THORN

96268309 R2L2 M 60L50 740 RWT CL1 GY

ISO 9223	IP66	IK08					T <sub>a</sub> -25 +50
C5							


### R2L2

A medium size LED road lighting lantern with 60 LEDs driven at 500mA with Wet Road optic. LED driver Programmable. Class I electrical, IP66, IK08. Housing: die-cast aluminium, powder coated textured light grey. Enclosure: tempered flat glass. Screws: stainless steel, Ecolubric® treated. Post top (Ø60/76mm, tilted 0°/5°/10°) or lateral (Ø34/42/49/60mm, tilted 0°/-5°/-10°/-15°) mounting. Complete with 4000K LED.

Dimensions: 880 x 370 x 155 mm  
Luminaire input power: 89 W  
Luminaire luminous flux: 14188 lm  
Luminaire efficacy: 159 lm/W  
Weight: 13.26 kg  
Scx: 0.06 m<sup>2</sup>



TLG\_R2L2\_F\_MPD.jpg



TLG\_R2L2\_M\_LDM.wmf

This product contains light sources of energy efficiency classes D, E.

All values marked with an \* are rated values. Thorn uses tried and tested components from leading suppliers, however there may be isolated instances of technology-related failures of individual LEDs during the rated product lifetime. International standards set the tolerance in initial flux and connected load at  $\pm 10\%$ . Unless stated otherwise, the values apply to an ambient temperature of 25°C.

Thorn Lighting is constantly developing and improving its products. The right is reserved to change specifications without prior notification or public announcement.  
© Thorn Lighting

**R2L2**

**96268309 R2L2 M 60L50 740 RWT CL1 GY**

**THORN**