

# Areaflood Pro

# THORN

96644800 AFP S 36L50-740 A4 CLO BS 3550 CL1 GY

|                |      |      |   |   |   |   |   |   |                           |
|----------------|------|------|---|---|---|---|---|---|---------------------------|
| ISO 9223<br>C5 | IP66 | IK08 | ⊕ | ⚠ | ⚙ | ⚙ | ⚙ | ⚙ | T <sub>a</sub> -25<br>+35 |
|----------------|------|------|---|---|---|---|---|---|---------------------------|

## Areaflood Pro

A compact, lightweight, general purpose LED area floodlight. With small body, driving 36 LEDs at 500mA with asymmetrical 40° light distribution. IP66, IK08, Class I electrical. Body: die-cast aluminium (EN AC-44300), Light grey 150 sanded textured (close to RAL9006).. Enclosure: 4mm thick toughened glass. Reversible mounting stirrup supplied, Driver programmed for constant light output. Complete with 4000K LED.

Not compatible with UrbaSens systems.

Dimensions: 462 x 265 x 139 mm  
Luminaire input power: 55 W  
Luminaire luminous flux: 8731 lm  
Luminaire efficacy: 159 lm/W  
Weight: 6.22 kg  
Scx: 0.05 m<sup>2</sup>



TLG\_AFLP\_F\_SMALLPDB.jpg



TLG\_AFLP\_M\_SML.wmf

This product contains light sources of energy efficiency class E.

All values marked with an \* are rated values. Thorn uses tried and tested components from leading suppliers, however there may be isolated instances of technology-related failures of individual LEDs during the rated product lifetime. International standards set the tolerance in initial flux and connected load at ±10%. Unless stated otherwise, the values apply to an ambient temperature of 25°C.

Thorn Lighting is constantly developing and improving its products. The right is reserved to change specifications without prior notification or public announcement.  
© Thorn Lighting