

## Areaflood Pro

96644855 AFP S 36L70-740 A6 HFX CL1 GY

|          |      |      |   |   |   |    |                           |
|----------|------|------|---|---|---|----|---------------------------|
| ISO 9223 | IP66 | IK08 | ⊕ | ⚡ | ⊗ | ⚙️ | T <sub>a</sub> -25<br>+35 |
| C5       |      |      |   |   |   |    |                           |

### Areaflood Pro

A compact, lightweight, general purpose LED area floodlight. With small body, driving 36 LEDs at 700mA with asymmetrical 60° light distribution. IP66, IK08, Class I electrical. Body: die-cast aluminium (EN AC-44300), Light grey 150 sanded textured (close to RAL9006).. Enclosure: 4mm thick toughened glass. Reversible mounting stirrup supplied, Complete with 4000K LED.

Dimensions: 462 x 265 x 139 mm  
 Luminaire input power: 77 W  
 Luminaire luminous flux: 11426 lm  
 Luminaire efficacy: 148 lm/W  
 Weight: 6.25 kg  
 Scx: 0.05 m<sup>2</sup>



TLG\_AFLP\_F\_SMALLPDB.jpg



TLG\_AFLP\_M\_SML.wmf

This product contains light sources of energy efficiency class E.

# Areaflood Pro

96644855 AFP S 36L70-740 A6 HFX CL1 GY

THORN