

## 96630827 PRISMA LED3000-840 HF FR L600 TW

|             |      |   |      |   |   |    |   |       |  |
|-------------|------|---|------|---|---|----|---|-------|--|
| EN<br>55015 | IP44 | ▽ | IK06 | ⊕ | ⚡ | ☀️ | 🔧 | 650°C |  |
|-------------|------|---|------|---|---|----|---|-------|--|

### Prisma

Slim Surface mounted LED luminaire. Electronic, fixed output control gear. Class I electrical, IP44. Body: pre-coated steel. End caps: white plastic. Diffuser: frosted acrylic. Keyhole fixing positions Ø14mm for direct mounting to ceiling, wall or brackets. Fixing centres: 500mm. Two cable entries Ø19mm in the rear of the body and knockouts in the endcaps. Grommets included. Electrical connection via 3 x 2 x 2.5mm² piano key terminal block.. Complete with 4000K LED

Dimensions: 616 x 166 x 64 mm  
 Luminaire input power: 27 W  
 Luminaire luminous flux: 3100 lm  
 Luminaire efficacy: 115 lm/W  
 Weight: 1.52 kg



TLG\_PRSM\_F\_01.jpg



TLG\_PRSM\_M\_LED\_LD1.wmf

**Prisma**

**96630827 PRISMA LED3000-840 HF FR L600 TW**

**THORN**