

## 96630840 PRISMA LED4400-840 HFIX FR L1200 TW

|             |      |   |      |   |   |    |   |       |  |
|-------------|------|---|------|---|---|----|---|-------|--|
| EN<br>55015 | IP44 | ▽ | IK06 | ⊕ | ⚡ | ☀️ | 🔧 | 650°C |  |
|-------------|------|---|------|---|---|----|---|-------|--|

### Prisma

Slim Surface mounted LED luminaire. Electronic, DALI dimmable control gear. Class I electrical, IP44. Body: pre-coated steel. End caps: white plastic. Diffuser: frosted acrylic. Keyhole fixing positions Ø14mm for direct mounting to ceiling, wall or brackets. Fixing centres: 1100mm. Two cable entries Ø19mm in the rear of the body and knockouts in the endcaps. Grommets included. Electrical connection via 5 x 2 x 2.5mm<sup>2</sup> piano key terminal block.. Complete with 4000K LED

Dimensions: 1216 x 166 x 64 mm  
 Luminaire input power: 35.3 W  
 Luminaire luminous flux: 4250 lm  
 Luminaire efficacy: 120 lm/W  
 Weight: 2.81 kg



TLG\_PRSM\_F\_01.jpg



TLG\_PRSM\_M\_LED\_LD1.wmf

**Prisma**

**96630840 PRISMA LED4400-840 HFIX FR L1200 TW**

**THORN**