

## Equaline Mini

96630767 EQUAMINI L1180 LED1900-830

IP20 IK06     Ta35


### Equaline Mini

A slim Surface mounted LED batten luminaire. Electronic, fixed output control gear. Class I electrical. IP20, IK06. Body: extruded aluminium anodised finish. Diffuser: opal polycarbonate plastic. End-cap: Dual-colour injected polycarbonate plastic. Electrical connection via flap in rear of body. Continuous linking possible. Complete with 3000K LED

Dimensions: 1180 x 37 x 60 mm  
 Luminaire input power: 17.8 W  
 Luminaire luminous flux: 2045 lm  
 Luminaire efficacy: 115 lm/W  
 Weight: 1.05 kg



TLG\_EQUM\_F\_LT.jpg



TLG\_EQUM\_M\_LD1.wmf

This product contains a light source of energy efficiency class D.

All values marked with an \* are rated values. Thorn uses tried and tested components from leading suppliers, however there may be isolated instances of technology-related failures of individual LEDs during the rated product lifetime. International standards set the tolerance in initial flux and connected load at  $\pm 10\%$ . Unless stated otherwise, the values apply to an ambient temperature of 25°C.

# Equaline Mini

96630767 EQUAMINI L1180 LED1900-830

THORN