Aquaforce Pro



96630985 AQFPRO S LED2900-840 PC MB MWS




Aquaforce Pro

An IP66, dust and moisture resistant LED luminaire. Electronic, Integral presence detector for on/off control. With medium beam distribution. Class I electrical. Canopy: light grey polycarbonate. Diffuser: high transmission opal polycarbonate with refraction prisms. Patented snap-on mechanism EasyClick for clipless mounting of diffuser. For surface or suspended mounting. Quick-fix brackets supplied for surface mounting. Suitable for ceiling or wall (both vertically and horizontally). Approved for indoor use or in canopied outdoor areas (see installation instructions). Mounting kits for conduit, chain suspension and catenary suspension are available as accessories. Suitable for through wiring with H05VV or NYM cable (rated 10A). Integral presence detector for on/off control. ambient temperature: -20°C to +45°C. Complete with 4000K LED..

Note: please contact your consultant if you are planning to use the luminaire in environments with chemical pollutants, high or condensing humidity and major variations in temperature.

Dimensions: 1100 x 92 x 90 mm Luminaire input power: 20.4 W Luminaire luminous flux: 2950 lm Luminaire efficacy: 145 lm/W

Weight: 1.74 kg





TLG AQUP F PDB 1100MED.jpg