

R2L2

THORN

96630714 R2L2 M 84L35-740 NR BS 3550 CL1 GY

| | | | | | | | |
|----------------|------|------|---|---|---|---|---------------------------|
| ISO 9223 C5 | IP66 | IK08 |  |  |  |  | T _a -25 +50 |
|----------------|------|------|---|---|---|---|---------------------------|

R2L2

A medium size LED road lighting lantern with 84 LEDs driven at 350mA with Narrow Road optic. LED driver Programmable. Class I electrical, IP66, IK08. Housing: die-cast aluminium, powder coated textured light grey. Enclosure: tempered flat glass. Screws: stainless steel, Ecolubric® treated. Post top (Ø60/76mm, tilted 0°/5°/10°) or lateral (Ø34/42/49/60mm, tilted 0°/-5°/-10°/-15°) mounting. Equipped with 50% power reduction circuit, effective 3 hours before and 5 hours after a calculated midnight. It can be deactivated at installation with an easily accessible internal switch. Complete with 4000K LED.

Dimensions: 880 x 370 x 155 mm

Luminaire input power: 87.4 W

Luminaire luminous flux: 14792 lm


Luminaire efficacy: 169 lm/W

Weight: 13.41 kg

Scx: 0.06 m²



TLG_R2L2_F_MPD.jpg



TLG_R2L2_M_LDM.wmf

This product contains light sources of energy efficiency classes D, E.

All values marked with an * are rated values. Thorn uses tried and tested components from leading suppliers, however there may be isolated instances of technology-related failures of individual LEDs during the rated product lifetime. International standards set the tolerance in initial flux and connected load at $\pm 10\%$. Unless stated otherwise, the values apply to an ambient temperature of 25°C.

Thorn Lighting is constantly developing and improving its products. The right is reserved to change specifications without prior notification or public announcement.
© Thorn Lighting