

## 96668625 PLI F 24L35-722-40 R/S T60 CL2 ANT

ISO 9223 C5	IP66	IK08					T <sub>a</sub> 25	
----------------	------	------	---	---	---	---	-------------------	--

### Plurio


Plurio Indirect: A decorative post-top LED lantern with radially symmetric distribution. LED driver with 24 LEDs driven at 350mA. Class II electrical, IP66, IK08. Base: cast aluminium, powder coated anthracite (close to RAL7043). Canopy: flat shape, aluminium, textured anthracite (close to RAL7043). Diffuser: UV stabilised, clear polycarbonate with anti-glare prisms. Indirect, reflector based optic. Complete with 2200-4000K NightTune LEDs. Post top mounting to Ø60mm column.

Upward lighting emissions below 1%.

Dimensions: Ø601 x 487 mm  
 Luminaire input power: 26 W  
 Luminaire luminous flux: 2973 lm  
 Luminaire efficacy: 114 lm/W  
 Weight: 11 kg  
 Scx: 0.167 m<sup>2</sup>



TLG\_PLRL\_F\_IFC\_ANT.jpg



TLG\_PLRL\_M\_IFC\_T60.wmf

This product contains a light source of energy efficiency class D.

**Plurio**

**96668625 PLI F 24L35-722-40 R/S T60 CL2 ANT**

**THORN**