

Royal Pro IP54

THORN

96649279 ROYAL PRO LED1500-940 6X3 IP54 HFI FP

RoHS	↓ IP20 ↑ IP54			T _a -20 +45	
------	------------------	--	--	---------------------------	--

Royal Pro IP54


An ultra slim ceiling recessed LED modular luminaire. DALI dimmable LED driver. Body: white painted aluminium frame. Diffuser: High uniformity microprismatic, UGR<19. Suitable for Office, Retail and School applications. Class II electrical, IP54_IP20. Electrical connection: Fitted with flex and plug. Complete with 4000K LED. CRI90+, 2 Step MacAdam LED.

This product has a Cyanosis Observation Index (COI) of less than 3.3, in accordance with AS/NZS 1680.2.5:1997 for hospitals and medical tasks.

Dimensions: 595 x 295 x 11 mm
Luminaire input power: 13.2 W
Luminaire luminous flux: 1548 lm
Luminaire efficacy: 117 lm/W
Weight: 2 kg



TLG_RYLL_F_02.jpg



TLG_RYLL_M_LD2.wmf

All values marked with an * are rated values. Thorn uses tried and tested components from leading suppliers, however there may be isolated instances of technology-related failures of individual LEDs during the rated product lifetime. International standards set the tolerance in initial flux and connected load at $\pm 10\%$. Unless stated otherwise, the values apply to an ambient temperature of 25°C.

Thorn Lighting is constantly developing and improving its products. The right is reserved to change specifications without prior notification or public announcement.
© Thorn Lighting