Aerie

96632909 ARW 12L105-740 WSC CL CL1 W5 T76 ANT



Aerie


A discreet, post top LED lantern with a timeless design. LED driver for 12 LEDs, driven at with Wide Street Comfort (asymmetrical) distribution. Class I electrical, IP66, IK10. Canopy and base: corrosion resistant die-cast powder coated aluminium suitable for C5 environments, finished textured anthracite (close to RAL7043). Enclosure: wide UV stabilised polycarbonate with clear finish. Complete with 4000K LED. Post top mounting to Ø76mm column. Prewired with 5m cable.

Dimensions: Ø602 x 586 mm Luminaire input power: 41 W Luminaire luminous flux: 5582 lm Luminaire efficacy: 136 lm/W Weight: 11.12 kg Scx: 0.172 m²



|H()|

TLG_AERI_F_W_CL.jpg



This product contains a light source of energy efficiency class D.

All values marked with an * are rated values. Thorn uses tried and tested components from leading suppliers, however there may be isolated instances of technology-related failures of individual LEDs during the rated product lifetime. International standards set the tolerance in initial flux and connected load at ±10%. Unless stated otherwise, the values apply to an ambient temperature of 25°C.

Thorn Lighting is constantly developing and improving its products. The right is reserved to change specifications without prior notification or public announcement. © Thorn Lighting