

Contrast

96633445 CONT3 12L105 830 MB SWD 6K ANT

|          |      |      |   |   |   |   |   |
|----------|------|------|---|---|---|---|---|
| ISO 9223 | IP66 | IK08 |  |  |  |  |  |
| C5       |      |      |   |   |   |   | T <sub>a</sub> -20<br>+35   |


Contrast

A medium architectural Bracket mounted LED Floodlight with 12 LEDs driven at and a medium beam distribution. LED driver, SwitchDim dimmable. Class II electrical, IP66, IK08. Body: die-cast aluminium (EN AC-44300), powder coated, textured anthracite (close to RAL7043). Compatible with coastal environments. Glass: tempered, 5mm thick. Gasket: EPDM. Screws: geomet. Equipped with 6kV surge protection device. Complete with 3000K LED

Dimensions: Ø239 x 156 mm  
Luminaire input power: 41 W  
Luminaire luminous flux: 3457 lm  
Luminaire efficacy: 84 lm/W  
Weight: 5 kg



TLG\_CON3\_F\_S\_12L.jpg



TLG\_CONL\_M\_12L.wmf

This product contains a light source of energy efficiency class D.

All values marked with an \* are rated values. Thorn uses tried and tested components from leading suppliers, however there may be isolated instances of technology-related failures of individual LEDs during the rated product lifetime. International standards set the tolerance in initial flux and connected load at ±10%. Unless stated otherwise, the values apply to an ambient temperature of 25°C.

Thorn Lighting is constantly developing and improving its products. The right is reserved to change specifications without prior notification or public announcement.  
© Thorn Lighting