

# Punch

THORN

96630503 <PUNCH 3 ASYM MSP 2200-840 L12 HF

UK CA	IP20	IK03	⊕	⚡	⚡	⚡	650°C	T <sub>a</sub> 0 +25	
----------	------	------	---	---	---	---	-------	-------------------------	--

## Punch


A slim, suspended luminaire with asymmetrical distribution. Fixed output LED driver. Body: sheet steel, powder coated white (close to RAL9016). Endcaps: sheet steel powder coated white (close to RAL9016). Louvre: glossy aluminium, double parabolic. Class I electrical, IP20, Impact strength: IK03. Electrical connection via pre-installed power cord (2.5m). Complete with 4000K LED. Suspension kit to be ordered separately

Y-Suspension connector included - Suspension cord with ceiling rose to be ordered separately (22171581).

Dimensions: 1180 x 116 x 44 mm  
Luminaire input power: 16 W  
Luminaire luminous flux: 2149 lm  
Luminaire efficacy: 134 lm/W  
Weight: 3.5 kg



TLG\_PNCH\_F\_ASYM.jpg



TLG\_PNC3\_M\_LDASY.wmf

This product contains a light source of energy efficiency class D.

All values marked with an \* are rated values. Thorn uses tried and tested components from leading suppliers, however there may be isolated instances of technology-related failures of individual LEDs during the rated product lifetime. International standards set the tolerance in initial flux and connected load at  $\pm 10\%$ . Unless stated otherwise, the values apply to an ambient temperature of 25°C.

Thorn Lighting is constantly developing and improving its products. The right is reserved to change specifications without prior notification or public announcement.  
© Thorn Lighting