

Indilouver Pro

96650815 INDI PRO LED3700-940 12x3 AH FP

RoHS	IP20	IK02			750 °C	T _a -20 +40
------	------	------	--	--	--------	---------------------------

Indilouver Pro

A stylish ceiling recessed LED luminaire. Fixed output LED driver. Class I electrical, IP20, Impact strength: IK02. Body: white painted steel, with option for concealed air return. Diffuser: 2mm thick, clear PMMA, linear profile. Baffle: aluminium extrusion. Fitted with flex and plug. Complete with 4000K LED, COI approved.

Dimensions: 1195 x 295 x 76 mm
 Luminaire input power: 35 W
 Luminaire luminous flux: 3982 lm
 Luminaire efficacy: 114 lm/W
 Weight: 5.8 kg



TLG_INPR_F_WH.jpg



TLG_INPR_M_M-L.wmf

All values marked with an * are rated values. Thorn uses tried and tested components from leading suppliers, however there may be isolated instances of technology-related failures of individual LEDs during the rated product lifetime. International standards set the tolerance in initial flux and connected load at $\pm 10\%$. Unless stated otherwise, the values apply to an ambient temperature of 25°C.

Indilouver Pro

96650815 INDI PRO LED3700-940 12x3 AH FP

THORN