

## Indilouver Pro

96650603 INDI PRO LED4500-940 15x3 FP

|      |      |      |  |  |        |                           |
|------|------|------|--|--|--------|---------------------------|
| RoHS | IP20 | IK02 |  |  | 750 °C | T <sub>a</sub> -20<br>+40 |
|------|------|------|--|--|--------|---------------------------|

### Indilouver Pro

A stylish ceiling recessed LED luminaire. Fixed output LED driver. Class I electrical, IP20, Impact strength: IK02. Body: white painted steel. Diffuser: 2mm thick, clear PMMA, linear profile. Baffle: aluminium extrusion. Fitted with flex and plug. Complete with 4000K LED, COI approved.

Dimensions: 1495 x 295 x 76 mm  
 Luminaire input power: 44 W  
 Luminaire luminous flux: 4684 lm  
 Luminaire efficacy: 106 lm/W  
 Weight: 6.5 kg



TLG\_INPR\_F\_WH.jpg



TLG\_INPR\_M\_M-L.wmf

All values marked with an \* are rated values. Thorn uses tried and tested components from leading suppliers, however there may be isolated instances of technology-related failures of individual LEDs during the rated product lifetime. International standards set the tolerance in initial flux and connected load at  $\pm 10\%$ . Unless stated otherwise, the values apply to an ambient temperature of 25°C.

Thorn Lighting is constantly developing and improving its products. The right is reserved to change specifications without prior notification or public announcement.  
 © Thorn Lighting

# Indilouver Pro

96650603 INDI PRO LED4500-940 15x3 FP

THORN