

# Indilouver Pro

THORN

96650834 INDI PRO LED4500-940 15x3 AH FP

RoHS	IP20	IK02			750 °C	T <sub>a</sub> -20 +40	
------	------	------	---	---	--------	---------------------------	--


## Indilouver Pro

A stylish ceiling recessed LED luminaire. Fixed output LED driver. Class I electrical, IP20, Impact strength: IK02. Body: white painted steel, with option for concealed air return. Diffuser: 2mm thick, clear PMMA, linear profile. Baffle: aluminium extrusion. Fitted with flex and plug. Complete with 4000K LED, COI approved.

Dimensions: 1495 x 295 x 76 mm  
Luminaire input power: 44 W  
Luminaire luminous flux: 4684 lm  
Luminaire efficacy: 106 lm/W  
Weight: 6.5 kg



TLG\_INPR\_F\_WH.jpg



TLG\_INPR\_M\_M-L.wmf

All values marked with an \* are rated values. Thorn uses tried and tested components from leading suppliers, however there may be isolated instances of technology-related failures of individual LEDs during the rated product lifetime. International standards set the tolerance in initial flux and connected load at  $\pm 10\%$ . Unless stated otherwise, the values apply to an ambient temperature of 25°C.

Thorn Lighting is constantly developing and improving its products. The right is reserved to change specifications without prior notification or public announcement.  
© Thorn Lighting