

## 96650056 WF G2 LED6500 830-57 L15 HFI

RoHS	IP65	IK08	⏚	⚡	☀️	🔧	750°C	T <sub>a</sub> -20 +40	
------	------	------	---	---	----	---	-------	---------------------------	--

### WeatherForce

A wide body, linear, water resistant LED luminaire, specifically designed for general outdoor applications. DALI dimmable LED driver. Class I electrical, IP65, Impact strength: IK08. Body: light grey injection moulded polycarbonate, supplied with tamper resistant screws. Diffuser: opal polycarbonate. Gear Tray: sheet steel, powder coated white. WeatherForce G2 is able to be surface mounted or suspended. Complete with switchable light colour temperature 3000K - 4000K - 5700K LED.


Dimensions: 1570 x 150 x 110 mm

Luminaire input power: 60 W

Weight: 4.5 kg



TLG\_WFG2\_F\_L15.jpg



TLG\_WFG2\_M\_L15.wmf

All values marked with an \* are rated values. Thorn uses tried and tested components from leading suppliers, however there may be isolated instances of technology-related failures of individual LEDs during the rated product lifetime. International standards set the tolerance in initial flux and connected load at  $\pm 10\%$ . Unless stated otherwise, the values apply to an ambient temperature of 25°C.

Thorn Lighting is constantly developing and improving its products. The right is reserved to change specifications without prior notification or public announcement.  
© Thorn Lighting