

IQ Beam

THORN

96635101 IQ BEAM 3000-930 MPT-F HFIX Q600 TBL5

IEC EN 60598-1 RG 1		IP20	IK03				650°C	T _a -20 +40	
---------------------------	---	------	------	---	---	---	-------	---------------------------	--


IQ Beam

A linear optic, recessed modular LED luminaire for exposed T, plasterboard and concealed grid ceilings. DALI-2 dimmable, LED driver. Class I electrical, IP20, Impact strength: IK03. Body: white painted steel. Diffuser: micro prism structure acrylic with diffusing foil. Suitable for lay-in installation, pull up installation optional. Complete with 3000K LED.

Dimensions: 597 x 597 x 60 mm
Luminaire input power: 27.5 W
Luminaire luminous flux: 2850 lm
Luminaire efficacy: 104 lm/W
Weight: 4.18 kg



TLG_IQBM_F_pers_B.jpg



TLG_IQBM_M_LDQN.wmf

This product contains a light source of energy efficiency class D.

All values marked with an * are rated values. Thorn uses tried and tested components from leading suppliers, however there may be isolated instances of technology-related failures of individual LEDs during the rated product lifetime. International standards set the tolerance in initial flux and connected load at $\pm 10\%$. Unless stated otherwise, the values apply to an ambient temperature of 25°C.

Thorn Lighting is constantly developing and improving its products. The right is reserved to change specifications without prior notification or public announcement.
© Thorn Lighting

IQ Beam

96635101 IQ BEAM 3000-930 MPT-F HFIX Q600 TBL5

THORN