

IQ Beam

96635437 IQ BEAM 4300-840 MC HF E3D Q600

| | | | | | | | |
|---------------------------|--|------|------|--|--|-------|-------------------------|
| IEC EN 60598-1 RG 1 | | IP20 | IK03 | | | 650°C | T _a 0 +35 |
|---------------------------|--|------|------|--|--|-------|-------------------------|

IQ Beam

A linear optic, recessed modular LED luminaire for exposed T, plasterboard and concealed grid ceilings. Fixed output, LED driver with 3 hour, Self/DALI Addressable test, emergency lighting circuit. Class I electrical, IP20, Impact strength: IK03. Body: white painted steel. Diffuser: mini cell reflector. Suitable for lay-in installation, pull up installation optional. Complete with 4000K LED.

Dimensions: 597 x 597 x 60 mm
 Luminaire input power: 35.6 W
 Luminaire luminous flux: 4300 lm
 Luminaire efficacy: 121 lm/W
 Weight: 4.5 kg



TLG_IQBM_F_MC.jpg



TLG_IQBM_M_LDQMC.wmf

This product contains a light source of energy efficiency class C.

All values marked with an * are rated values. Thorn uses tried and tested components from leading suppliers, however there may be isolated instances of technology-related failures of individual LEDs during the rated product lifetime. International standards set the tolerance in initial flux and connected load at $\pm 10\%$. Unless stated otherwise, the values apply to an ambient temperature of 25°C.