

Novaline Style

96635536 NOVS M 3500-840 DI HFI BK

IEC EN 60598-1 RG 1	RoHS	UK CA	IP54		halogen	IK08					850°C	T _a -15 +25
---------------------------	------	----------	------	--	---------	------	--	--	--	--	-------	---------------------------

Novaline Style

Decorative circular luminaire with medium body. Low indirect component for wall and ceiling illumination. Electronic, DALI dimmable. Aesthetic trim of the luminaire made of polycarbonate in black. Diffuser: opal polycarbonate. Class II electrical, IP54. Complete with 4000K LED.

Dimensions: Ø397 x 69 mm
 Luminaire input power: 24.6 W
 Luminaire luminous flux: 3500 lm
 Luminaire efficacy: 142 lm/W
 Weight: 2.14 kg



TLG_NOVS_F_4BK.jpg



TLG_NOVS_M_LD400.wmf

This product contains a light source of energy efficiency class C.

All values marked with an * are rated values. Thorn uses tried and tested components from leading suppliers, however there may be isolated instances of technology-related failures of individual LEDs during the rated product lifetime. International standards set the tolerance in initial flux and connected load at ±10%. Unless stated otherwise, the values apply to an ambient temperature of 25°C.

Novaline Style

96635536 NOVS M 3500-840 DI HFI BK

THORN