

Candle Bollard

96679076 CN B 8L35 830 RSC CL1 MPL ANT

ISO 9223	C5	IP66	IK10				T _a 25	
----------	----	------	------	--	--	--	-------------------	--


Candle Bollard

Environmentally respectful bollard with limited upward lighting emission with 8 LEDs driven at 350mA with Radial symmetrical comfort light distribution. Fixed output LED driver. Class I electrical, IP66, IK10. Base: die-cast aluminium (EN AC-44300). Finish: powder coated aluminium, texturized anthracite (close to RAL7043). Diffuser: UV stabilised clear polycarbonate. Flange mounted. Complete with 3000K LED.

Dimensions: Ø234 x 1017 mm
 Luminaire input power: 10.1 W
 Weight: 7.98 kg
 Scx: 0.06 m²
 Luminaire efficacy: 93 lm/W



TLG_CNDB_F_MPL.jpg



TLG_CNDB_M_MPL.wmf

This product contains a light source of energy efficiency class D.

All values marked with an * are rated values. Thorn uses tried and tested components from leading suppliers, however there may be isolated instances of technology-related failures of individual LEDs during the rated product lifetime. International standards set the tolerance in initial flux and connected load at ±10%. Unless stated otherwise, the values apply to an ambient temperature of 25°C.