

Punch

96636026 PUNCH 3 LV MSC 6000-930 L15 HFIX

UK CA	IP20	IK03	⊕	⚡	⚙️	⚙️	⚙️	650°C	T _a 0 +25
----------	------	------	---	---	----	----	----	-------	-------------------------

Punch


A slim, surface mounted luminaire with direct distribution. DALI dimmable Electronic,. Body: sheet steel, powder coated white (close to RAL9016). Endcaps: sheet steel powder coated white (close to RAL9016). Louvre: glossy aluminium,. Class I electrical, IP20, Impact strength: IK03. Electrical connection via piano key terminal block. Complete with 3000K LED.

Can be used as a suspended direct only luminaire when combined with Y-Suspension connector and suspension kit (to be ordered separately 22171581 & 22171349).

Dimensions: 1581 x 162 x 56 mm
 Luminaire input power: 44.2 W
 Luminaire luminous flux: 5840 lm
 Luminaire efficacy: 132 lm/W
 Weight: 3.8 kg



TLG_PNCH_F_LOUVRE_surface_on.jpg



TLG_PNC3_M_LV_RESD.wmf

This product contains light sources of energy efficiency class D.

All values marked with an * are rated values. Thorn uses tried and tested components from leading suppliers, however there may be isolated instances of technology-related failures of individual LEDs during the rated product lifetime. International standards set the tolerance in initial flux and connected load at ±10%. Unless stated otherwise, the values apply to an ambient temperature of 25°C.

Punch

96636026 PUNCH 3 LV MSC 6000-930 L15 HFIX

THORN