

IQ Beam

96636078 IQ BEAM HT 6300-840 MPT-F PIR SS Q600

| | | | | | | | |
|---------------------------|--|------|------|--|--|-------|-------------------------|
| IEC EN 60598-1 RG 1 | | IP20 | IK03 | | | 650°C | T _a 0 +50 |
|---------------------------|--|------|------|--|--|-------|-------------------------|


IQ Beam

A linear optic, recessed modular LED luminaire for exposed T, plasterboard and concealed grid ceilings. Fixed output, LED driver. Class I electrical, IP20, Impact strength: IK03. Body: white painted steel. Diffuser: micro prism structure acrylic with diffusing foil. Suitable for lay-in installation, pull up installation optional. Equipped with PIR presence detector (SmartSwitch) for standalone on/off control. Complete with 4000K LED.

Dimensions: 597 x 597 x 60 mm
 Luminaire input power: 50 W
 Luminaire luminous flux: 6300 lm
 Luminaire efficacy: 126 lm/W
 Weight: 4.32 kg



TLG_IQBM_F_HT_PIR_pers.jpg



TLG_IQBM_M_HT_P.wmf

This product contains a light source of energy efficiency class C.

All values marked with an * are rated values. Thorn uses tried and tested components from leading suppliers, however there may be isolated instances of technology-related failures of individual LEDs during the rated product lifetime. International standards set the tolerance in initial flux and connected load at ±10%. Unless stated otherwise, the values apply to an ambient temperature of 25°C.