

# HiPak Gen4

THORN

96652595 HIPAK GEN4 M LED25000-840 RK MWS

UK CA	IP65	▽	IK08	⊕	⚡	⚡	⚡	850°C	T <sub>a</sub> -20 +45	
----------	------	---	------	---	---	---	---	-------	---------------------------	--

## HiPak Gen4

An IP65 single point suspension LED high bay luminaire with rack beam optic. Electronic, fixed output (corridor function via remote control) , for 220-240V, 50/60Hz supply. Class I electrical. IK08. Housing: die-cast aluminium. Lens/Diffuser: polycarbonate. Supplied without mounting hook, stirrup or rod has to be ordered separately (rigid mounting is recommended). Equipped with 5 pole Quick Connect socket. Equipped with Microwave sensor. Complete with 4000K LED.

ambient temperature: -20°C to +45°C

Dimensions: Ø320 x 170 mm

Luminaire input power: 147.9 W


Luminaire luminous flux: 25000 lm

Luminaire efficacy: 169 lm/W

Weight: 4.02 kg



TLG\_HIP4\_F\_NO\_STIR\_2.jpg



TLG\_HIP4\_M\_ALL.wmf

All values marked with an \* are rated values. Thorn uses tried and tested components from leading suppliers, however there may be isolated instances of technology-related failures of individual LEDs during the rated product lifetime. International standards set the tolerance in initial flux and connected load at ±10%. Unless stated otherwise, the values apply to an ambient temperature of 25°C.

Thorn Lighting is constantly developing and improving its products. The right is reserved to change specifications without prior notification or public announcement.  
© Thorn Lighting

# HiPak Gen4

96652595 HIPAK GEN4 M LED25000-840 RK MWS

THORN