

HiPak Gen4

THORN

96652600 HIPAK GEN4 M LED20000-840 WB BC



HiPak Gen4

An IP65 single point suspension LED high bay luminaire with wide beam optic. Electronic, DALI-2 dimmable D4i , for 220-240V, 50/60Hz supply. Class I electrical. IK08. Housing: aluminium. Lens/Diffuser: polycarbonate. Supplied with mounting hook. Equipped with 5 pole Quick Connect socket. Wireless controlled via App with Bluetooth® 4.x - basicDIM Wireless Complete with 4000K LED.

ambient temperature: -20°C to +45°C

Dimensions: Ø320 x 170 mm

Luminaire input power: 110.4 W


Luminaire luminous flux: 20000 lm

Luminaire efficacy: 181 lm/W

Weight: 4.15 kg



TLG_HIP4_F_BC_3.jpg



TLG_HIP4_M_ALL.wmf

All values marked with an * are rated values. Thorn uses tried and tested components from leading suppliers, however there may be isolated instances of technology-related failures of individual LEDs during the rated product lifetime. International standards set the tolerance in initial flux and connected load at ±10%. Unless stated otherwise, the values apply to an ambient temperature of 25°C.

Thorn Lighting is constantly developing and improving its products. The right is reserved to change specifications without prior notification or public announcement. © Thorn Lighting

HiPak Gen4

96652600 HIPAK GEN4 M LED20000-840 WB BC

THORN